



- Исполнение 'A' с отверстием для СОЖ
- Исполнение 'S' без отверстия для СОЖ

На изображении правостороннее исполнение

d _A [mm]	Тип, обозначение	L N R 	h [mm]	l ₁ [mm]	l ₂ [mm]	f [mm]	D _{min} [mm]		
25	A25R PCLNL 12	L	23	200	36	17	32	CN.. 1204..	E01
25	A25R PCLNR 12	R	23	200	36	17	32	CN.. 1204..	E01
32	A32S PCLNL 12	L	30	250	50	22	40	CN.. 1204..	E01
32	A32S PCLNR 12	R	30	250	50	22	40	CN.. 1204..	E01
40	A40T PCLNL 12	L	38	300	60	27	50	CN.. 1204..	E02
40	A40T PCLNR 12	R	38	300	60	27	50	CN.. 1204..	E02
25	S25T PCLNL 12	L	23	300	22	17	32	CN.. 1204..	E01
25	S25T PCLNR 12	R	23	300	22	17	32	CN.. 1204..	E01
32	S32U PCLNL 12	L	30	350	24,1	22	40	CN.. 1204..	E01
32	S32U PCLNR 12	R	30	350	24,1	22	40	CN.. 1204..	E01
40	S40V PCLNL 12	L	38	400	24,1	27	50	CN.. 1204..	E02
40	S40V PCLNR 12	R	38	400	24,1	27	50	CN.. 1204..	E02
50	S50W PCLNL 16	L	47	450	31	35	63	CN.. 1606..	E03
50	S50W PCLNR 16	R	47	450	31	35	63	CN.. 1606..	E03

E01	59442	59568	59437	59430	86176	4771	140586
E02	59446	59568	59437	59430	86176	4771	140587
E03	59443	59451	59438	59426	86177	4771	140589

